

Black Softwall



Product Specifications

Application

For the discharge of dry bulk cement from tank truck and in-plant service.

Construction

> Tube

1/8" (static dissipating/static conductive) Black Chemituf® synthetic rubber. Available in 1/8", 3/16" and 1/4" tube gauges

> Cover

Black SBR synthetic rubber with white spiral stripe (wrapped impression)

> Reinforcement

Spiral-plied synthetic fabric

Temperature Range

-25°F to 180°F (-32°C to 82°C)

Packaging

100' lengths, coiled and poly-wrapped

Branding (Spiral)

Example: Continental ContiTech Black Softwall

Couplings

Refer to the ContiTech Industrial Hose Assembly Manual for crimp specifications. Use ContiTech Insta-Lock™ cam & groove fittings with this product. See the Coupling Systems information pages at the back of this catalog.

Order Codes

549-152 (1/8" tube gauge 50 psi)
 549-149 (3/16" tube gauge 75 psi)
 549-148 (1/4" tube gauge 50 psi)

Black Softwall

Order Codes: 549-152

| SAP # | | Dia. | ID | OD | Weight |
|----------|-------------------|------|-------|-------|--------|
| (1/8") | Survivor Compound | PO | mm | mm | #/ft. |
| 20019306 | | 3 | 76.1 | 86.3 | 1.05 |
| 20019309 | 20665783 | 4 | 102.1 | 112.3 | 1.38 |
| 20046192 | | 4½ | 114.6 | 125.4 | 1.64 |
| 20019315 | 20677559 | 5 | 127.4 | 138.2 | 1.82 |
| 20019319 | | 6 | 152.7 | 163.9 | 2.25 |

Black Softwall

Order Codes: 549-149

| SAP # | | Dia. | ID | OD | Weight |
|----------|-------------------|------|-------|-------|--------|
| (3/16") | Survivor Compound | PO | mm | mm | #/ft. |
| 20019281 | 20673663 | 4 | 102.1 | 116.2 | 1.92 |
| 20029627 | | 4½ | 114.6 | 129.0 | 2.21 |
| 20109496 | | 5 | 127.4 | 141.8 | 2.44 |
| 20468267 | | 5½ | 140.1 | 154.5 | 2.67 |
| 20446687 | | 6 | 152.7 | 167.7 | 3.01 |

Black Softwall

Order Codes: 549-148

| SAP # | | Dia. | ID | OD | Weight |
|----------|-------------------|------|-------|-------|--------|
| (1/4") | Survivor Compound | PO | mm | mm | #/ft. |
| 20019277 | 20639327 | 4 | 102.1 | 118.7 | 2.29 |
| 20311113 | | 4½ | 114.6 | 131.8 | 2.65 |
| 20019279 | | 5 | 127.4 | 145.0 | 3.00 |
| 20019280 | | 6 | 152.7 | 170.3 | 3.56 |

Hose design ratio (burst pressure) 4:1.

Air & Multipurpose
 General Purpose
 Heavy Duty
 Push-on

Chemical Transfer

Cleaning Equipment

Food
 Dry Transfer
 Liquid Transfer
 Washdown

Marine

Material Handling
 Abrasives
 Bulk Transfer
 Cement & Concrete

Mining

Petroleum
 Aircraft Fueling
 Dispensing
 Dock
 Rig Supply
 Transfer Discharge
 Transfer S&D

Specialty

Steam

Vacuum

Water
 Discharge
 Suction & Discharge
 Washdown
 Garden

Welding

Coupling Systems

Equipment

Appendix